

無  
C13

無  
C15

無  
C18

無  
C13

## Power Rating

Maximum Power	388 kW	433 kW	470 kW	328 kW
Rated Speed	1800-2100 rpm	1800-2100 rpm	1800-2000 rpm	1800-2100
Minimum Power	287 kW	354 kW	429 kW	287 kW

## Emission Standards

Emissions	U.S. EPA Tier 4 Final, EU Stage V, Japan 2014 and Korea Tier 4 Final emissions standards	U.S. EPA Tier 4 Final, EU Stage V	U.S. EPA Tier 4 Final, EU Stage V	China Stage II, U.S. EPA Tier 2 Equivalent or U.S. EPA Tier 3 Equivalent, EU Stage II Equivalent or EU Stage IIIA Equivalent
-----------	--	-----------------------------------	-----------------------------------	--

## General

Engine Configuration	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel
Bore	130 mm	137 mm	145 mm	130 mm
Stroke	157 mm	171 mm	183 mm	157 mm
Displacement	12.5 l	15.2 l	18.1 l	12.5 l
Compression Ratio	17.0:1	17.0:1	16.0:1	17.0:1
Aspiration	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)
Rotation from Flywheel End	Counterclockwise	Counterclockwise	Counterclockwise	Counterclockwise
Aftertreatment	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	-

## Power Unit Dimensions

Length	854 mm	854 mm	854 mm	1295 mm
Width	287 mm	287 mm	287 mm	1186 mm
Height	551 mm	551 mm	551 mm	1054 mm
Weight	19.4 kg	19.4 kg	19.4 kg	1692 kg

## PETU Dimensions - Tier 4 Final Only

Length	854 mm	854 mm	854 mm	1295 mm
Width	287 mm	287 mm	287 mm	1186 mm
Height	551 mm	551 mm	551 mm	1054 mm
Weight	19.4 kg	19.4 kg	19.4 kg	1692 kg
Volume Capacity	48.4 l	48.4 l	48.4 l	-