

無	無	無	無
C7.1 Tier 3 / IMO II	C32 IMO II	C32 Tier 3	C280

Dimensions & Weights

Length	1095 mm	-	-	-
Height	891 mm	-	-	-
Minimum Width	798 mm	-	1528 mm	1704 mm
Maximum Width	850 mm	-	1528 mm	1741 mm
Minimum Engine Dry Weight	730 kg	-	-	-
Maximum Engine Dry Weight	760 kg	-	-	-

Power Rating

Power Range	208 bkW (280 bhp) @ 2300 rpm	-	-	-
-------------	------------------------------	---	---	---

Engine Specifications

Configuration	In-line 6, 4-stroke-cycle diesel	Vee 12, 4-Stroke-Cycle Diesel	Vee 12, 4-Stroke-Cycle Diesel	In-Line 6, Vee 8, Vee 12, Vee 16, 4-Stroke-Cycle Diesel
Emissions	U.S. EPA Tier 3 / IMO II emissions certified (commercial), RCD 2016 compliant, EU Stage IIIA compliant, CCNR Stage II through reciprocity with EU Stage IIIA	-	-	-
Rated Engine Speed	2300 rpm	-	-	-
Bore	105 mm	145 mm	145 mm	280 mm
Stroke	135 mm	162 mm	162 mm	300 mm
Displacement	7.01 l	32.1 l	32.1 l	-
Aspiration	Turbocharged-aftercooled aspiration	TTA	TTA	TA
Governor	Electronic (A5E2 V2 ECM)	-	-	-

Refill Capacity	Lube Oil System w/Oil filter change: 20 L (5.3 gal)	-	-	-
Oil Change Interval	500 hrs	-	-	-
Cooling	Heat exchanger or keel cooled	-	-	-
Flywheel Housing	SAE No. 03 with SAE 11.5 in flywheel	-	-	-
Rotation	Counterclockwise from flywheel end	-	-	-