

無
C32 ACERT Tier 3

無
3512C IMO II

無
3516C IMO II

無
C280-12 Tier 4

Power Rating

Power Range	750-1800 bhp (559-1342 bkW)	1280-2551 bhp (955-1902 bkW)	1650-3386 bhp (1230-2525 bkW)	4962-5444 bhp (3700-4060 bkW)
-------------	-----------------------------	------------------------------	-------------------------------	-------------------------------

Engine Specifications

Speed Range	1600-2300 rpm	1200 rpm, 1600 rpm, 1800 rpm	1200-1800 rpm	1000 rpm
Emissions	EPA Tier 3, IMO II, EU IW	IMO II, EU IW	IMO II	EPA Tier 4, IMO II
Aspiration	TTA	TTA	TTA	TTA
Bore	145 mm	170 mm	215 mm	280 mm
Stroke	162 mm	190 mm	170 mm	300 mm
Displacement	32.1 l	51.8 l	78 l	222 l
Rotation from Flywheel End	Counterclockwise	Counterclockwise or Clockwise	Counterclockwise or clockwise	Counterclockwise or clockwise
Configuration	Vee 12, 4-Stroke-Cycle Diesel	Vee 12, 4-Stroke-Cycle Diesel	Vee 16, 4-Stroke-Cycle Diesel	Vee 12, 4-Stroke-Cycle Diesel

Dimensions & Weights

Maximum Height	1587 mm	2242 mm	2150 mm	3404 mm
Minimum Length	2121 mm	2590 mm	3637 mm	4623 mm
Minimum Height	1547 mm	1904 mm	1967 mm	3404 mm
Maximum Width	1528 mm	2232 mm	2142 mm	2032 mm
Maximum Length	2284 mm	2669 mm	3761 mm	4623 mm
Minimum Dry Weight	3152 kg	6532 kg	7961 kg	25980 kg
Minimum Width	1528 mm	2037 mm	2037 mm	2032 mm