

無
C13

無
C9

無
C11

無
C13

Power Rating

Maximum Power	388 kW	261 kW	287 kW	328 kW
Rated Speed	1800-2100 rpm	1800-2200 rpm	1800-2100 rpm	1800-2100
Minimum Power	287 kW	205 kW	242 kW	287 kW

Emission Standards

Emissions	U.S. EPA Tier 4 Final, EU Stage V, Japan 2014 and Korea Tier 4 Final emissions standards	China Stage II, U.S. EPA Tier 2 Equivalent or U.S. EPA Tier 3 Equivalent, EU Stage II Equivalent or EU Stage IIIA Equivalent	China Stage II, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent	China Stage II, U.S. EPA Tier 2 Equivalent or U.S. EPA Tier 3 Equivalent, EU Stage II Equivalent or EU Stage IIIA Equivalent
-----------	--	--	--	--

General

Engine Configuration	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel
Bore	130 mm	112 mm	130 mm	130 mm
Stroke	157 mm	149 mm	140 mm	157 mm
Displacement	12.5 l	8.8 l	11 l	12.5 l
Compression Ratio	17.0:1	16.3:1	17.2:1	17.0:1
Aspiration	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)
Rotation from Flywheel End	Counterclockwise	Counterclockwise	Counterclockwise	Counterclockwise
Aftertreatment	DOC+DPF+SCR	-	-	-

Power Unit Dimensions

Length	854 mm	-	1203 mm	1295 mm
Width	287 mm	988 mm	1054 mm	1186 mm
Height	551 mm	-	1186 mm	1054 mm
Weight	19.4 kg	1490 kg	1692 kg	1692 kg

PETU Dimensions - Tier 4 Final Only

Length	854 mm	-	1203 mm	1295 mm
Width	287 mm	988 mm	1054 mm	1186 mm
Height	551 mm	-	1186 mm	1054 mm
Weight	19.4 kg	1490 kg	1692 kg	1692 kg
Volume Capacity	48.4 l	-	-	-