

無
C7.1

無
C9.3B

無
C15

無
C13D

Power Rating

Maximum Power	205 kW	298 kW	433 kW	515 kW
Rated Speed	1800-2200 rpm	1800-2200 rpm	1800-2100 rpm	1800-2100 rpm
Minimum Power	151 kW	224 kW	354 kW	340 kW

Emission Standards

Emissions	U.S. EPA Tier 4 Final	U.S. EPA Tier 4 Final	U.S. EPA Tier 4 Final, EU Stage V	EU Stage V, U.S. EPA Tier 4 Final, Korea Stage V, Japan 2014, China NRIV
-----------	-----------------------	-----------------------	-----------------------------------	--

General

Engine Configuration	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle-Diesel	Inline 6, 4-Stroke-Cycle Diesel	In-Line 6
Bore	105 mm	115 mm	137 mm	130 mm
Stroke	135 mm	149 mm	171 mm	162 mm
Displacement	7.01 l	9.3 l	15.2 l	12.9 l
Compression Ratio	16.5:1	17.0:1	17.0:1	18:1
Aspiration	Series Turbocharged Aftercooled (TTA)	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged-Aftercooled (TA)
Rotation from Flywheel End	Counterclockwise	Counterclockwise	Counterclockwise	Counterclockwise
Aftertreatment	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR	DOC+DPF+SCR

Power Unit Dimensions

Length	1461 mm	854 mm	854 mm	2249 mm
Width	714 mm	287 mm	287 mm	1160 mm
Height	644 mm	551 mm	551 mm	1641 mm
Weight	134 kg	19.4 kg	19.4 kg	-

Aftertreatment Dimensions

Width	714 mm	287 mm	287 mm	1160 mm
Height	644 mm	551 mm	551 mm	1641 mm
Weight	134 kg	19.4 kg	19.4 kg	-

Aftertreatment Dimensions*

Diameter	338 mm	330 mm	356 mm	-
----------	--------	--------	--------	---