

無
C9無
C15無
C1.7無
C13D

Power Rating

Maximum Power	261 kW	403 kW	36 kW	515 kW
Rated Speed	1800-2200 rpm	1800-2100 rpm	2800 rpm	1800-2100 rpm
Minimum Power	205 kW	328 kW	36.4 kW	340 kW

Emission Standards

Emissions	China Stage II, U.S. EPA Tier 2 Equivalent or U.S. EPA Tier 3 Equivalent, EU Stage II Equivalent or EU Stage IIIA Equivalent	China Stage II, U.S. EPA Tier 3 Equivalent, EU Stage IIIA Equivalent	EU Stage V, U.S. EPA Tier 4 Final, Japan 2014 (Tier 4 Final)	EU Stage V, U.S. EPA Tier 4 Final, Korea Stage V, Japan 2014, China NRIV
-----------	--	--	--	--

General

Engine Configuration	Inline 6, 4-Stroke-Cycle Diesel	Inline 6, 4-Stroke-Cycle Diesel	In-Line 4, 4-Stroke-Cycle Diesel	In-Line 6
Bore	112 mm	137.2 mm	84 mm	130 mm
Stroke	149 mm	171.4 mm	100 mm	162 mm
Displacement	8.8 l	15.2 l	1.662 l	12.9 l
Compression Ratio	16.3:1	18.0:1	17.0:1	18:1
Aspiration	Turbocharged Aftercooled (TA)	Turbocharged Aftercooled (TA)	Turbocharged	Turbocharged-Aftercooled (TA)
Rotation from Flywheel End	Counterclockwise	Counterclockwise	Counterclockwise	Counterclockwise
Aftertreatment	-	-	DOC+DPF	DOC+DPF+SCR

Power Unit Dimensions

Width	988 mm	1317 mm	596 mm	1160 mm
Weight	1490 kg	2055 kg	224 kg	-